

1.5 GHz Active Probe

► TAP1500



TAP1500 Single-ended Active FET Probe provides excellent high-speed electrical and mechanical performance required for today's digital system designs. Specifically designed for use and direct connection to the TekVPI® probe interface used on Tektronix' new DPO7000 and DPO/MSO4000 Series Oscilloscopes, the TAP1500 Active FET probe achieves high-speed signal acquisition and measurement fidelity by solving three traditional problems:

- Lower DUT loading effects with ≤ 1 pF input capacitance and $1\text{ M}\Omega$ input resistance
- Versatile DUT connectivity for attaching to small SMDs
- Preserves oscilloscope bandwidth at the probe tip for DPO7000 and DPO/MSO4000 Series Oscilloscope models, up to 1 GHz

► Characteristics

Bandwidth (probe only) – ≥ 1.5 GHz.
Attenuation (probe only) – $10\times \pm 2\%$.
Rise Time (probe only) – ≤ 267 ps.
Input Capacitance – < 1 pF.
Input Resistance – $1\text{ M}\Omega$.
Linear Dynamic Range – ± 8 V (16 V_{p-p}).
Input Offset Range – ± 10 V.
Max Input Voltage (non-destruct) – ± 15 V (DC + pkAC).
Propagation Delay – 5.3 ns.

Physical Characteristics

Probe Head Size	mm	in.
Height	11.25	0.44
Width	5.1	0.20
Length	60.4	2.38

Weight	kg	lbs.
Net	0.45	1

Other Dimensions

Cable Length	1300	51
--------------	------	----

Power Requirements

TAP1500 is powered directly by the DPO7000 and DPO/MSO4000 Series Oscilloscopes using TekVPI probe interface.

Recommended Oscilloscopes
DPO7000 and DPO/MSO4000 Series Oscilloscopes with TekVPI probe interface.

Environmental

Temperature –

Operating – 0°C to $+50^\circ\text{C}$.

Non-Operating – -40°C to $+71^\circ\text{C}$.

Humidity –

Operating – 5% to 95% Relative Humidity (RH) at up to $+30^\circ\text{C}$; 5% to 85% RH above $+30^\circ\text{C}$ up to $+50^\circ\text{C}$; non-condensing.

Non-Operating – 5% to 95% Relative Humidity (RH) at up to $+30^\circ\text{C}$; 5% to 85% RH above $+30^\circ\text{C}$ up to $+75^\circ\text{C}$; non-condensing.

Altitude –

Operating – Up to 3,000 m (10,000 feet).

Non-Operating – Up to 15,240 m (50,000 feet).

Regulatory

Compliance Labeling – WEEE (European Union).

Standard Warranty

One year parts and labor.

► Features & Benefits

Outstanding electrical performance

- ≥ 1.5 GHz probe bandwidth
- < 267 ps rise time
- ≤ 1 pF input capacitance
- $1\text{ M}\Omega$ input resistance
- -8 V to $+8$ V input dynamic range
- -10 V to $+10$ V DC input offset range

Versatile mechanical performance

- Small compact probe head for probing small geometry circuit elements
- DUT attachment accessories enable connection to SMDs as small as 0.5 mm pitch
- Robust design for reliability

Easy-to-Use

- Connects directly to DPO7000 and DPO/MSO4000 series oscilloscopes using the TekVPI® probe interface
- Provides automatic units scaling and readout on the oscilloscope display
- Easy access to oscilloscope probe menu display for probe status/diagnostic information, and to control probe DC offset

► Applications

High-speed digital systems design

Component design and characterization

Manufacturing engineering and test

Educational research

Signals with voltage swings up to 16 V_{p-p}

1.5 GHz Active Probe

► TAP1500

Ordering Information

TAP1500

1.5 GHz Active Probe.

TAP1500X2

1.5 GHz Active Probe. Discounted two TAP1500 probe package.

► Standard Accessories Included

Description	Qty with TAP1500 or TAP1500X2	Reorder Part Number	Reorder Qty
Low Inductance 1 in. Z-Ground Lead	2 each	196-3439-xx	1 each (Pkg of 10)
3 in. Ground Lead	2 each	196-3437-xx	1 each (Pkg of 2)
6 in. Ground Lead	2 each	196-3436-xx	1 each (Pkg of 2)
Y-Lead Adapter	2 each	196-3463-xx	1 each (Pkg of 2)
Color Coding Clips	2 each of 5 colors	016-1315-xx	2 each of 5 colors
Solderable Probe Tips	10 each	131-5638-xx	1 each (Pkg of 10)
Micro CKT Test Tip	4 each	206-0569-xx	1 each
Right Angle Square Pin Adapter	2 each	214-4227-xx	1 each
100 mm Square Pin Ground Adapter	2 each	131-5777-xx	1 each
User Manual*1	1 each	071-1809-xx English or 071-1810-xx Japanese or 071-1811-xx Simplified Chinese	1 each
Nylon Carrying Case*2	1 each	016-1952-xx	1 each

*1 Manual language must be specified when ordering.

*2 The TAP1500X2 does not include individual probe cases. Users who desire the individual probe case should order the TAP1500 probe.

Options

Manual Options

Opt. L5 – Japanese instruction manual.

Opt. L7 – Simplified Chinese instruction manual.

Service Options

Opt. C3 – Calibration Service 3 Years.

Opt. C5 – Calibration Service 5 Years.

Opt. D1 – Calibration Data Report.

Opt. D3 – Calibration Data Report 3 Years (with Opt. C3).

Opt. D5 – Calibration Data Report 5 Years (with Opt. C5).

Opt. R3 – Repair Service 3 Years.

Opt. R5 – Repair Service 5 Years.

Recommended Accessories

Description	Package Qty	Reorder Part Number
SMT KlipChip™ Adapter	20	SMG50
IC Micro-Grabber	2	013-0309-00
Probe Case	1	016-1952-02

For Further Information

Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tektronix.com

Product(s) are manufactured in ISO registered facilities.



Copyright © 2008, Tektronix. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks or registered trademarks of their respective companies.

04/08 HB/WOW

51W-19043-2

Tektronix®

Contact Tektronix:

ASEAN / Australasia (65) 6356 3900

Austria +41 52 675 3777

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777

Belgium 07 81 60166

Brazil & South America (11) 40669400

Canada 1 (800) 661-5625

Central East Europe, Ukraine and the Baltics +41 52 675 3777

Central Europe & Greece +41 52 675 3777

Denmark +45 80 88 1401

Finland +41 52 675 3777

France +33 (0) 1 69 86 81 81

Germany +49 (221) 94 77 400

Hong Kong (852) 2585-6688

India (91) 80-22275577

Italy +39 (02) 25086 1

Japan 81 (3) 6714-3010

Luxembourg +44 (0) 1344 392400

Mexico, Central America & Caribbean 52 (55) 5424700

Middle East, Asia and North Africa +41 52 675 3777

The Netherlands 090 02 021797

Norway 800 16098

People's Republic of China 86 (10) 6235 1230

Poland +41 52 675 3777

Portugal 80 08 12370

Republic of Korea 82 (2) 6917-5000

Russia & CIS +7 (495) 7484900

South Africa +27 11 206 8360

Spain (+34) 901 988 054

Sweden 020 08 80371

Switzerland +41 52 675 3777

Taiwan 886 (2) 2722-9622

United Kingdom & Eire +44 (0) 1344 392400

USA 1 (800) 426-2200

For other areas contact Tektronix, Inc. at: 1 (503) 627-7111

Updated 12 November 2007